(19) World Intellectual Property Organization

International Bureau





(43) International Publication Date 6 October 2005 (06.10.2005)

PCT

(10) International Publication Number WO 2005/092732 A1

(51) International Patent Classification⁷: B65D 43/02

(21) International Application Number:

PCT/GB2005/000986

(22) International Filing Date: 16 March 2005 (16.03.2005)

(25) Filing Language: English

(26) Publication Language: English

(**30**) Priority Data: 0406762.5

25 March 2004 (25.03.2004) GB

(71) Applicant (for all designated States except US): CAR-BONITE CORPORATION [PA/PA]; El Dorado Building, 2nd Floor, 52nd & Elvira Mendez Streets, P.O. Box 1358 WTC, Panama (PA).

(72) Inventors; and

- (75) Inventors/Applicants (for US only): SMITH, Matthew, Eric [GB/GB]; Ballacurn Cottage, Ballaugh, Isle of Man IM7 5EU (GB). MONDSZEIN, Karl [GB/GB]; 7 West Bank Lea, Mansfield, Nottinghamshire NG19 7BY (GB).
- (74) Agents: JENNINGS, Nigel, Robin et al.; Kilburn & Strode, 20 Red Lion Street, London WC1R 4PJ (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: BEVERAGE CONTAINERS



(57) Abstract: A beverage container comprises a receptacle (2) which has a central axis (3) and is sealed by a lid (6) of resilient material. The receptacle includes a neck (8) defining an opening and the lid includes a closure plate (30, 32), integral with which is a depending skirt (18) extending around the outer surface of the neck. The inner surface of the skirt (18) carries a continuous annular flange (20), which is in sealing engagement with the underside of a continuous downwardly directed annular shoulder (14) on the outer surface of the neck and thus prevents movement of the lid in the axial direction away from the receptacle. The annular flange (20) on the lid is connected thereto by a resilient hinge connection (22). The annular flange (20) is elongate in axial sectional view. The end surface of the free end of the flange (20) is in sealing engagement with the underside of the shoulder (14) and the resilience of the resilient hinge connection (22) urges the side surface of the free end of the annular flange (20) into sealing engagement with the external surface of the neck.



